

Bakker Oilfield Supply

Coevorden B.V.

a Bakker Groep Coevorden company



High pressure equipment

1", 1" X 2", 1½", and 2" Plug Valves

Weir SPM high pressure plug valves are tough, fieldproven units that provide dependable service for applications such as cementing, fracturing, acidizing, coiled tubing, and sand control. Available in 1", 1" X 2", 1¹/₂" and 2" sizes and in pressure ratings to 15,000 psi NSCWP*, Weir SPM plug valves feature quality components throughout for greater dependability, minimum weight, and maximum strength. Plug valves are available in standard service and sour gas service models. Special models are available to 20,000 psi.

3" and 4" Plug Valves

Weir SPM three-inch and four-inch plug valves are available in pressure ratings to 20,000 psi NSCWP*. Features include a flanged body for easier maintenance, integral inlets and outlets, hand crank, locked-open and shut gear drive standard, and multiple lubricating inlets. Standard service and sour gas service models are available. Weir SPM's latest plug valve offering is the 3" SP150 Manual Actuated Plug Valve.

Remote Operation

Hydraulic and pneumatic actuators are available for all sizes of plug valves, which enhances safety in the field.



Repair and Seal Kits

Weir SPM repair kits and seal kits contain all the parts necessary to rebuild valves in the field or in the shop. Weir SPM seal kits contain all items in the standard repair kit, except the plug. Individual components and elastomer kits are also available.

Valve	NSCWP*	End	1″	1" x 2"	1½"	2″	3″	4″
Model	(PSI)	Connections						
SP50TF	5,000	Threaded	*			*		
SP100TF	10,000	Threaded				*		
SP150TF	15,000	Threaded			*	*		
SP150TM	15,000	Threaded		*				
SP150TMF	15,000	Threaded		*				
SP150WU	15,000	Fig. 1502	*	*	*	*	*	*
SP200WU	20,000	Fig. 2001				*	*	

