



Bakker Oilfield Supply Coevorden B.V.

a Bakker Groep Coevorden company

Duplex-Separator 10 bar 8m³

Onshore

Separators / KO-Vessels

The Duplex-Separator in the rental fleet of B.O.S. is specially designed for the separation of liquids and gas in the oil, gas and geothermal industry. Common liquids like water and glycol and natural gas can be separated.

The Duplex-Separator is also used for protection of downstream equipment like compressors and flow meters. The Separator is capable of separating gas out of liquids

Bakker Groep Coevorden B.V. can provide specialized personnel for any rig up, rig down or operator job. We use a Competence Management System which secures the competence level of our technical employees. We are able to supply you with the right man for the job.



Technical specifications separator

Data Separator:

Design pressure	: 10 bar
Design temperature	: -20 / +115 °C
Volume	: 8 m ³
Service	: Sour
Medium	: Natural Gas / liquid

Data Nozzles:

Inlet	: DN200 PN16 / 6" fig 206
Gas outlet	: DN 100 PN16 / 2" fig 1502
Liquid outlet	: DN200 PN16 / 6" fig 206
Purge line	: DN50 PN16 = 2" fig 1502
Drain	: 2" 150# / 2"fig 1502
PSV outlet	: 6"-150# RF

Transport dimensions:

Frame (LxWxH)	: 750 x 250 x 300 cm
MGW	: 7.000 kg

Please contact our sales department for any further information about our full service concept or the individual rental rates of our equipment.

